FEB 2 4 1988

FEM 1.209:421245

# FLOOD INSURANCE STUDY

## BOROUGH OF MC SHERRYSTOWN, PENNSYLVANIA
### ADAMS COUNTY



MARCH 4, 1988

COMPLETED

Federal Emergency Management Agency

COMMUNITY NUMBER - 421245

ORIGINAL

## NOTICE TO
## FLOOD INSURANCE STUDY USERS

Communities participating in the National Flood Insurance Program (NFIP) have established repositories of flood hazard data for floodplain management and flood insurance study purposes. This Flood Insurance Study (FIS) may not contain all data available within the repository. It is advisable to contact the community repository for any additional data.

TABLE OF CONTENTS


| | | Page |
|---|---|---|
| 1.0 | INTRODUCTION | 1 |
| | 1.1 Purpose of Study | 1 |
| | 1.2 Authority and Acknowledgments | 1 |
| | 1.3 Coordination | 1 |
| 2.0 | AREA STUDIED | 2 |
| | 2.1 Scope of Study | 2 |
| | 2.2 Community Description | 2 |
| | 2.3 Principal Flood Problems | 2 |
| | 2.4 Flood Protection Measures | 2 |
| 3.0 | ENGINEERING METHODS | 2 |
| | 3.1 Hydrologic Analyses | 4 |
| | 3.2 Hydraulic Analyses | 4 |
| 4.0 | FLOODPLAIN MANAGEMENT APPLICATIONS | 5 |
| | 4.1 Floodplain Boundaries | 5 |
| | 4.2 Floodways | 6 |
| 5.0 | INSURANCE APPLICATION | 6 |
| 6.0 | FLOOD INSURANCE RATE MAP | 8 |
| 7.0 | OTHER STUDIES | 9 |
| 8.0 | LOCATION OF DATA | 9 |
| 9.0 | BIBLIOGRAPHY AND REFERENCES | 9 |

## TABLE OF CONTENTS - continued


Page

### FIGURES

Figure 1 - Vicinity Map 3

Figure 2 - Floodway Schematic 7

### TABLES

Table 1 - Summary of Discharges 4

### EXHIBITS

Exhibit 1 - Flood Profiles
Plum Creek Panel 01P

Exhibit 2 - Flood Insurance Rate Map and Street Index

Exhibit 3 - Elevation Reference Marks

FLOOD INSURANCE STUDY
BOROUGH OF McSHERRYSTOWN, ADAMS COUNTY, PENNSYLVANIA

# 1.0 INTRODUCTION

## 1.1 Purpose of Study

This Flood Insurance Study investigates the existence and severity of flood hazards in the Borough of McSherrystown, Adams County, Pennsylvania, and aids in the administration of the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973. This study has developed flood risk data for various areas of the community that will be used to establish actuarial flood insurance rates and assist the community in its efforts to promote sound floodplain management. Minimum floodplain management requirements for participation in the National Flood Insurance Program (NFIP) are set forth in the Code of Federal Regulations at 44 CFR, 60.3.

In some states or communities, floodplain management criteria or regulations may exist that are more restrictive or comprehensive than the minimum Federal requirements. In such cases, the more restrictive criteria take precedence and the state (or other jurisdictional agency) will be able to explain them.

## 1.2 Authority and Acknowledgments

The sources of authority for this Flood Insurance Study are the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973.

The hydrologic and hydraulic analyses for this study were prepared by the U. S. Geological Survey (USGS) for the Federal Emergency Management Agency (FEMA), under Inter-Agency Agreement No. EMW-85-E-1823, Project Order No. 8. This work was completed in January 1987.

## 1.3 Coordination

On November 13, 1984, an initial Consultation and Coordination Officer's (CCO) meeting was held with representatives of FEMA, the borough, and the USGS (the study contractor) to determine the streams to be studied by detailed methods. On April 15, 1987, a final CCO meeting was held with representatives of FEMA, the borough, and the study contractor to review the results of the study.

## 2.0 AREA STUDIED

### 2.1 Scope of Study

This Flood Insurance Study covers the incorporated area of the Borough of McSherrystown, Adams County, Pennsylvania. The area of study is shown on the Vicinity Map (Figure 1).

Plum Creek was studied by detailed methods for its entire length within the community. The areas studied by detailed methods were selected with priority given to all known flood hazard areas and areas of projected development and proposed construction through January 1992.

### 2.2 Community Description

The Borough of McSherrystown is located in the southeastern part of Adams County in south-central Pennsylvania, approximately 10 miles southeast of Gettysburg. It is completely surrounded by the Township of Conewago.

### 2.3 Principal Flood Problems

Major floods cause localized inundation of low-lying areas along Plum Creek.

### 2.4 Flood Protection Measures

No flood control structures are located on Plum Creek within the Borough of McSherrystown.

## 3.0 ENGINEERING METHODS

For the flooding source studied in detail in the community, standard hydrologic and hydraulic study methods were used to determine the flood hazard data required for this study. A flood event of a magnitude which is expected to be equaled or exceeded once on the average during any 100-year period (recurrence interval) has been selected as having special significance for floodplain management and for flood insurance rates. This event, commonly termed the 100-year flood, has a 1 percent chance of being equaled or exceeded during any year. Although the recurrence interval represents the long term average period between floods of a specific magnitude, rare floods could occur at short intervals or even within the same year. The risk of experiencing a rare flood increases when periods greater than 1 year are considered. For example, the risk of having a flood which equals or exceeds the 100-year flood (1 percent chance of annual exceedence) in any 50-year period is approximately 40 percent (4 in 10), and, for any 90-year period, the risk increases to




FIGURE 1

FEDERAL EMERGENCY MANAGEMENT AGENCY

**BOROUGH OF MC SHERRYSTOWN, PA**

**(ADAMS CO.)**

APPROXIMATE SCALE

2000 0 2000 4000 6000 FEET

**VICINITY MAP**

approximately 60 percent (6 in 10). The analyses reported herein reflect flooding potentials based on conditions existing in the community at the time of completion of this study. Maps and flood elevations will be amended periodically to reflect future changes.

3.1 Hydrologic Analyses

Hydrologic analyses were carried out to establish the peak discharge-frequency relationships for the flooding source studied in detail affecting the community.

The flood frequency discharge value for Plum Creek was determined utilizing regional regression equations developed in USGS Water Resources Investigations 82-21 (Reference 1). The Pennsylvania State University PSU-IV method confirmed the determination (Reference 2). This technique was developed for specific use in estimating peak flood flows for ungaged sites on small streams in Pennsylvania.

A summary of the drainage area-peak discharge relationships for Plum Creek is shown in Table 1, "Summary of Discharges."

TABLE 1 - SUMMARY OF DISCHARGES

| FLOODING SOURCE AND LOCATION | DRAINAGE AREA (sq. miles) | PEAK DISCHARGE (cfs) 100-YEAR |
|---|---|---|
| PLUM CREEK | | |
| Upstream of an unnamed tributary, approximately 0.5 mile downstream of corporate limits | 7.65 | 2,000 |

3.2 Hydraulic Analyses

Analyses of the hydraulic characteristics of flooding from the source studied were carried out to provide estimates of the elevations of floods of the selected recurrence intervals.

Cross sections for Plum Creek were field surveyed and located at close intervals above and below bridges and culverts to compute the significant backwater effects of these structures. All bridges, dams, and culverts in the community were field surveyed to obtain elevation data and structural geometry.

Locations of selected cross sections used in the hydraulic analyses are shown on the Flood Profiles (Exhibit 1) and the Flood Insurance Rate Map (Exhibit 2) where applicable.

Water-surface elevations of floods of the selected recurrence intervals for Plum Creek were computed by modeling channel and bridge hydraulics using the WSPRO step-backwater computer program (References 3 and 4). Flood profiles were drawn showing computed water-surface elevations for floods of the selected recurrence intervals. The starting water-surface elevation for Plum Creek was estimated from the regional relationship between drainage area and flood depth prepared by the USGS (Reference 5).

Channel roughness factors (Manning's "n") used in the hydraulic computations were assigned on the basis of engineering judgment and field inspection of the floodplain areas. The channel "n" values for Plum Creek ranged from 0.038 to 0.055, and the overbank "n" values ranged from 0.045 to 0.140.

The hydraulic analyses for this study were based on unobstructed flow. The flood elevations shown on the profiles are thus considered valid only if hydraulic structures remain unobstructed, operate properly, and do not fail.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). Elevation reference marks used in this study are shown on the maps; the descriptions of the marks are presented in Elevation Reference Marks (Exhibit 3).

## 4.0 FLOODPLAIN MANAGEMENT APPLICATIONS

The NFIP encourages State and local governments to adopt sound floodplain management programs. Therefore, each Flood Insurance Study provides 100-year flood elevations and delineations of the 100-year floodplain boundaries to assist communities in developing floodplain management measures.

### 4.1 Floodplain Boundaries

To provide a national standard without regional discrimination, the 1 percent annual chance (100-year) flood has been adopted by FEMA as the base flood for floodplain management purposes. For the stream studied in detail, the 100-year floodplain boundaries have been delineated using the flood elevations determined at each cross section. Between cross sections, the boundaries were interpolated using topographic maps at a scale of 1:24,000 with a contour interval of 20 feet (Reference 6).

The 100-year floodplain boundaries are shown on the Flood Insurance Rate Map (Exhibit 2). On this map, the 100-year floodplain boundary corresponds to the boundary of the areas of special flood hazards (Zone AE). Small areas within the floodplain boundaries may lie

above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data.

### 4.2 Floodways

Encroachment on floodplains, such as structures and fill, reduces flood-carrying capacity, increases flood heights and velocities, and increases flood hazards in areas beyond the encroachment itself. One aspect of floodplain management involves balancing the economic gain from floodplain development against the resulting increase in flood hazard. For purposes of the National Flood Insurance Program, a floodway is used as a tool to assist local communities in this aspect of floodplain management. Under this concept, the area of the 100-year floodplain is divided into a floodway and a floodway fringe. The floodway is the channel of a stream, plus any adjacent floodplain areas, that must be kept free of encroachment so that the 100-year flood can be carried without substantial increases in flood heights. Minimum federal standards limit such increases to 1.0 foot, provided that hazardous velocities are not produced.

The area between the floodway and 100-year floodplain boundaries is termed the floodway fringe. The floodway fringe encompasses the portion of the floodplain that could be completely obstructed without increasing the water-surface elevation of the 100-year flood by more than 1.0 foot at any point. Typical relationships between the floodway and the floodway fringe and their significance to floodplain development are shown in Figure 2.

No floodways were calculated as part of this study.

## 5.0 INSURANCE APPLICATION

For flood insurance rating purposes, flood insurance zone designations are assigned to a community based on the results of the engineering analyses. These zones are as follows:

Zone A

Zone A is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by approximate methods. Because detailed hydraulic analyses are not performed for such areas, no base flood elevations or depths are shown within this zone.

Zone AE

Zone AE is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by detailed methods. In most instances, whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.


100 YEAR FLOOD PLAIN
FLOODWAY FRINGE
FLOODWAY
FLOODWAY FRINGE
STREAM CHANNEL
FLOOD ELEVATION WHEN CONFINED WITHIN FLOODWAY
ENCROACHMENT
ENCROACHMENT
C
D
SURCHARGE*
A
B
AREA OF FLOOD PLAIN THAT COULD BE USED FOR DEVELOPMENT BY RAISING GROUND
FLOOD ELEVATION BEFORE ENCROACHMENT ON FLOOD PLAIN
LINE A - B IS THE FLOOD ELEVATION BEFORE ENCROACHMENT
LINE C - D IS THE FLOOD ELEVATION AFTER ENCROACHMENT
*SURCHARGE NOT TO EXCEED 1.0 FOOT (FEMA REQUIREMENT) OR LESSER AMOUNT IF SPECIFIED BY STATE.

Floodway Schematic - Figure 2

Zone AH

Zone AH is the flood insurance rate zone that corresponds to the areas of 100-year shallow flooding (usually areas of ponding) where average depths are between 1 and 3 feet. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone AO

Zone AO is the flood insurance rate zone that corresponds to the areas of 100-year shallow flooding (usually sheet flow on sloping terrain) where average depths are between 1 and 3 feet. Average whole-foot depths derived from the detailed hydraulic analyses are shown within this zone.



BEST COPY AVAILABLE

Zone A99

Zone A99 is the flood insurance rate zone that corresponds to areas of the 100-year floodplain that will be protected by a Federal flood protection system where construction has reached specified statutory milestones. No base flood elevations or depths are shown within this zone.

Zone V

Zone V is the flood insurance rate zone that corresponds to the 100-year coastal floodplains that have additional hazards associated with storm waves. Because approximate hydraulic analyses are performed for such areas, no base flood elevations are shown within this zone.

Zone VE

Zone VE is the flood insurance rate zone that corresponds to the 100-year coastal floodplains that have additional hazards associated with storm waves. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone X

Zone X is the flood insurance rate zone that corresponds to areas outside the 500-year floodplain, areas within the 500-year floodplain, and to areas of 100-year flooding where average depths are less than 1 foot, areas of 100-year flooding where the contributing drainage area is less thar 1 square mile, and areas protected from the 100-year flood by levees. No base flood elevations or depths are shown within this zone.

Zone D

Zone D is the flood insurance rate zone that corresponds to unstudied areas where flood hazards are undetermined, but possible.

## 6.0 FLOOD INSURANCE RATE MAP

The Flood Insurance Rate Map is designed for flood insurance and floodplain management applications.

For flood insurance applications, the map designates flood insurance rate zones as described in Section 5.0 and, in the 100-year floodplains that were studied by detailed methods, shows selected whole-foot base flood elevations or average depths. Insurance agents use the zones and base flood elevations in conjunction with information on structures and their contents to assign premium rates for flood insurance policies.

For floodplain management applications, the map shows by tints, screens, and symbols, the 100-year floodplain. The locations of selected cross sections used in the hydraulic analyses are shown where applicable.

## 7.0 OTHER STUDIES

A Flood Insurance Study for the Township of Conewago is currently being prepared (Reference 7). The results of that study will be in exact agreement with the results of this study.

## 8.0 LOCATION OF DATA

Information concerning the pertinent data used in preparation of this study can be obtained by contacting FEMA, the Natural and Technological Hazards Division, Liberty Square Building (Second Floor), 105 South Seventh Street, Philadelphia, Pennsylvania 19106.

## 9.0 BIBLIOGRAPHY AND REFERENCES


1. U. S. Department of the Interior, Geological Survey, Water Resources Investigations 82-21, Evaluation of the Streamflow-Data Program in Pennsylvania by H. N. Flippo, Jr., Harrisburg, Pennsylvania, 1982.

2. The Pennsylvania State University, Institute for Research on Land & Water Resources, Report FHWA/PA 81-013, Procedure PSU-IV for Estimating Design Peaks on Ungaged Pennsylvania Watersheds by G. Aron and D. F. Kibler, University Park, Pennsylvania, 1981.

3. National Technical Information Service, Bridge Waterways Analysis Model/ Research Report (WSPRO) by J. O. Shearman, W. H. Kirby, V. R. Schneider, and H. N. Flippo, Jr., Springfield, Virginia, 1985.

4. National Technical Information Service, Bridge Waterways Analysis Model/ User's Instructions (WSPRO) by J. O. Shearman, W. H. Kirby, and V. R. Schneider, Springfield, Virginia, 1985.

5. U. S. Department of the Interior, Geological Survey, Water-Resources Investigations 86-4195, Technique for Estimating Depths of 100-Year Floods In Pennsylvania by H. N. Flippo, Jr., Harrisburg, Pennsylvania, 1986.

6. U. S. Department of the Interior, Geological Survey, 7.5-Minute Series Topographic Maps, Scale 1:24,000, Contour Interval 20 Feet: McSherrystown, Pennsylvania, 1944, Photorevised 1973.

7. Federal Emergency Management Agency, Flood Insurance Study, Township of Conewago, Adams County, Pennsylvania (Unpublished).

## EXHIBIT 3 - ELEVATION REFERENCE MARKS

| Reference Mark | Elevation (Feet NGVD) | Description of Location |
|---|---|---|
| RM 1 | 528.65 | Chiseled square cut on top of southwest wing wall, beside PDH disk, on State Route 116 bridge over Plum Creek. |




FEDERAL EMERGENCY MANAGEMENT AGENCY

**BOROUGH OF MC SHERRYSTOWN, PA**

(ADAMS CO.)

**FLOOD PROFILES**

**PLUM CREEK**

01P